

Res-Q 300 Plus

3ply Surgical Face Mask



ASTM LEVEL 2 (EARLOOP)

Our ASTM Level 2 Surgical Face Mask is designed to resist moderate fluid splashes at 120mmHg while maintaining smooth breathability. The highly efficient filtration media can filter or trap all the common bacteria and particle surrounding us.

FEATURES:

- ASTM LEVEL 2
- Moderate Fluid Resistance: 120mmHg
- Bacterial Filtration Efficiency: >99%
- Particle Filtration Efficiency: >99%
- Breathability - Delta P: <3.0mmH₂O/cm²
- Flammability: Class 1

| GENERAL DESCRIPTION | | | |
|---------------------|-------------|---|---|
| Name of Commodity | | Surgical Face Mask with Filter | |
| Our Ref No.: | | 2-406EL | |
| Level | | 2 MEDIUM BARRIER | |
| Standard | | ASTM F2100 | |
| Sterilization | | Non | |
| Utilization | | Intended to be used as isolation face mask, procedure mask and dental face mask | |
| Fixation | Loops | 2 pieces to be fixed by Ultrasonic Machine | |
| Composition | Outer Layer | Outer | PP Spunbond Non Woven Fabric |
| | | Model | STANDARD or SENSITIVE |
| | | Color | Light blue Green Yellow Lavender Pink Orange Black White |
| Filtration Layer | Middle | Stamp | Location "Cross Protection" to be embossed on the top right corner Type Embossed |
| | | Color | White |
| | | Filtration Efficiency | BFE ≥ 99% as according to ASTM F2101 PFE ≥ 99% as according to ASTM F2299 |
| Inner Layer | Inner | Color | STANDARD (PP Spunbond) or SENSITIVE (Lint Free) White |
| | | Fixed Way | 2pcs of loops are sealed on Left and Right by Ultrasonic Machine |
| Loops | Color | Material | 100% ROUND type cotton loops |
| | | Material | White |
| | | Material | 100% ROUND type cotton loops |
| Nose Piece | Color | Material | White |
| | | Material | Plastic Coated Strip |
| | | Location | At the Centre of the Upper Part of Face Mask |

| PACKING & STORAGE | |
|--------------------------------|--|
| INNER BOX | |
| Size | 185x85x105mm |
| Color | 5 color printing |
| Shipping Mark | CROSS PROTECTION |
| PACKING DESCRIPTION | |
| Inner | 50pcs per box |
| Carton | 20bxs per carton |
| Details | 10bxs per layer, 2 layer per cartons in vertical packing |
| STORAGE | |
| Temperature | Avoid excessive heat 40°C, 104°F |
| Humidity | Below 80% |
| Sunlight | Keep away from direct sunlight |
| MANIPULATION CONDITIONS | |
| Message Humidity | This product is not designed for use as protection against any toxic dust, fumes, mists, gases, vapors. Not for use in spray paint operations. |

